

## **How to Update the JMS539 Firmware on Mac: AU-S10X**

This Firmware Update must be applied to the chipset called “JMS539”, please check it on the PCB board first.



This Update can be applied to Mac OS 10.5 or higher. The Firmware Update will not affect stored data on the inserted drive (hard or solid-state drive may be used). Please follow the steps below to properly install the Firmware Update:

1. Insert a drive in the Mobile Enclosure (AU-S10X).
2. Connect the Mobile Storage via USB port to the host (Mac). Note: The Mobile Storage must be connected during the entire process in order for the Firmware Update Utility to work properly.
3. Double-click on the “JMS539FirmwareUpdateTool\_1-bay\_v02\_for\_Mac.” to un-zip the file.
4. Double-click on the “Mobile JMS539 Firmware Update Utility.dmg” to install the Firmware Update Utility (Tool).
5. After the Firmware Update Utility is installed, restart the Mac OS to continue the Firmware Update.
6. Go to Applications under Mac OS and double-click on the “Mobile JMS539 Firmware Update Utility” to start the Firmware Update process.
7. After the Tool begins, a pop-up window will appear as shown below and it will search for the Mobile Storage connected to the Mac OS. Note: All other USB external drive(s) must be disconnected before continuing.



8. Once the Mobile Storage is found, click on “continue” to proceed.



9. Once the Firmware Update is completed, a pop-up window will appear as shown below.



10. To end the Firmware Update process, click on “Exit” and re-connect the Mobile Storage again.

11. To confirm that the Firmware Update is properly installed, double-click on the “Mobile JMS539 Firmware Update Utility” in Applications under Mac OS. If a pop-up window stating “The device is already updated!” appears, the Firmware Update has been successfully installed. If the pop-up window does not appear, please try the Firmware Update installation process once again.



Welcome to the JMicron Firmware Update Utility.

This application is used to update your JMicron Device. Make sure the drive you want to update is the **ONLY** external USB drive connected to your computer before you continue.

The device already updated!

Continue

Exit